

WAVE POWER ADVANTAGE 15W-40

Mineral Passenger Car Engine oil

WAVE POWER ADVANTAGE 15W-40 is a high performance mineral engine oil suitable for gasoline-, LPG-, and diesel engines in modern passenger cars and light vans with or without turbochargers.

WAVE POWER ADVANTAGE 15W-40 is based on high performance virgin mineral base oil in combination with a specially selected additive technology to ensure the following properties:

- Good thermal and oxidation stability.
- Stay-in-grade.
- Good protection against wear, foam & corrosion.
- Low temperature properties, to ensure a smooth cold start.

WAVE POWER ADVANTAGE 15W-40 meets the following performance criteria:

API SL/CF ACEA A3/B3 MB 229.1

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	15W-40
Density @15 °C	kg/m ³	ASTM 4052	877
Kinematic Viscosity @ 40 °C	mm ² /s	ASTM D7042	98
Kinematic Viscosity @ 100 °C	mm ² /s	ASTM D7042	13.5
Viscosity Index		ASTM D2270	138
Viscosity CCS @ -20 °C		ASTM D5293	5774
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	%Wt	ASTM D874	0.96
Date Issued: 18-1-2021		Supersedes: 22-03-2019	Revision Nr.: 02

